



**SPECIFICATION AND NOTE**

NO

- 1/ DIA 20mm
- 2/ No Body Leakage at 4.15MPa when valve open & close
- No Inner Leakage when valve closed at 0.35MPa
- 3/ Design Pressure 4.15MPa
- 4/ Hyrdo Testing Pressure 6.23MP
- 5/ Busting Pressure 20.8MPa
- 6/ Media Temp -30°~+120°
- 7/ Ambient Temp -30°~+60° @ below 95%RH
- 8/ Valve Stem Torque≤6N.m
- 9/ No Dust, Dirts, Chips
- 10/ Absolute Open/Close during operation

**Factory Setting**

- 1/ Fully opened when delivery
- 2/ Valve Stem Nut: Tighten by hand tight
- 3/ Valve Core tighten at 0.35~0.45N.m
- 4/ O-Ring mfg by :NOK or Ruifu
- Grease by: Moly Kote EM-50L
- 5/ Valve Core mfg by GZL

8	3124201-10	Stem	1	SUS304		16	26051*-10	Cap	1	PE	*#
7	3125201-10	Seat	2	PTFE		15	260515-10	Cap	1	PE	38#
6	G859	O-Ring	2	HNBR	P7	14	3207106-10	Cu Tube	2	TP2Y/Y2	
5	3205101-10	Ball Seat	2	PTFE		13		Valve Core	1	for R410A	GZL
4	3207005-10	Tail Peice	1	Brass+Cu		12	103304-10A	Core Nut	1	GHPb59-1/C377	IS17
3	3202103-10A	Tail	1	C3602	H26	11	3005201-10	Seat	1	PTFE	
2	3203102-10	Ball	1	SUS304		10	3128101-10	Stop Ring	1	C3771	
1	3201103-10A	Body	1	C3602		9	009G7343-01A	Nut	1	GHPb59-1/C377	IS21
18	GB70-85	Bolt M4*8	2	SUS304							Doc
17	3208101-10A	Mounting	1	SUS304							Doc

DN 20

OKAYAMA SEIKO